

LED OMNIDIRECTIONAL A-LAMP
A19 & A21 GEN 4 SERIES



PRODUCT DESCRIPTION:

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 and A21 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.

FEATURES:

- 6W, 480lm, 40W Inc. replacement
- 9W, 800lm, 60W Inc. replacement
- 11W, 1100lm, 75W Inc. replacement
- 15W, 1600lm, 100W Inc. replacement
- Dimmable (Dimmable down to 10 percent)
- Power factor: ≥ 0.90
- 25,000 hour life (L70 standards)
- CRI: ≥ 80
- ENERGY STAR certified
- Standard E26 base, GU24 base available
- Suitable for dry and damp locations
- Not for use in fully enclosed luminaires
- Five year limited warranty

APPLICATIONS

- Pendants
- Table and floor lamps
- Sconces

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: 9A19DLED27/G4

		DLED		/G4
FAMILY	BASE	DIMMABILITY	CCT	GENERATION
6A19= 6 watts, A19 9A19= 9 watts, A19 11A19= 11 watts, A19 15A21 15 watts, A21	(OMIT)= E26 GU24= GU24	DLED= Dimmable	27= 2700K 30= 3000K 40= 4000K	/G4= Generation 4

NOTES:

1. 9A19DLED27/G4 is available in 4-Packs and bulk pack (50pcs)
2. 11A19DLED27/G4 is available in bulk pack (50pcs)
3. 15A21DLED27/G4 is available in bulk pack (50pcs)
4. See page 4 for compatible dimmer list

SPECIFICATIONS:

		6A19DLEDxx/G4	9A19DLEDxx/G4	11A19DLEDxx/G4	15A21DLEDxx/G4
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Power Consumption	6W	9W	11W	15W
	Lumens Delivered	480	800	1100	1600
	Efficacy (lm/w)	80	88	100	106
	CRI	≥80			
	Color Temperature (CCT)	2700K, 3000K, 4000K			
	Lumen Maintenance (L70)	25,000 Hours			
ELECTRICAL	Power Factor	≥0.9			
	Input Voltage	120V			
PHYSICAL	Base Type	E26			
	Operating Temperature	-4°F - 104°F			
CERTIFICATION	Certification	UL Listed, RoHS Compliant			
	Environment	Dry, Damp			
	Warranty	5 Year Limited			

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	OUTPUT (LUMENS)	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
E26 Base									
101464	6A19DLED27/G4	★	6	40W Inc.	480	80	80	2700K	2.36" x 4.40"
101465	6A19DLED30/G4	★	6	40W Inc.	480	80	80	3000K	2.36" x 4.40"
102022	6A19DLED40/G4	★	6	40W Inc.	480	80	80	4000K	2.36" x 4.40"
101466	9A19DLED27/G4	★	9	60W Inc.	800	88	82	2700K	2.36" x 4.40"
101307	9A19DLED27/G4/4P	★	9	60W Inc.	800	88	82	2700K	2.36" x 4.40"
101410	9A19DLED27/G4/BP	★	9	60W Inc.	800	88	82	2700K	2.36" x 4.40"
101467	9A19DLED30/G4	★	9	60W Inc.	800	88	82	3000K	2.36" x 4.40"
102023	9A19DLED40/G4	★	9	60W Inc.	800	88	82	4000K	2.36" x 4.40"
101432	11A19DLED27/G4	★	11	75W Inc.	1100	100	83	2700K	2.51" x 4.54"
101433	11A19DLED27/G4/BP	★	11	75W Inc.	1100	100	83	2700K	2.51" x 4.54"
101469	11A19DLED30/G4	★	11	75W Inc.	1100	100	83	3000K	2.51" x 4.54"
102024	11A19DLED40/G4	★	11	75W Inc.	1100	100	83	4000K	2.51" x 4.54"
101434	15A21DLED27/G4	★	15	100W Inc.	1600	106	84	2700K	2.83" x 5.31"
101435	15A21DLED27/G4/BP	★	15	100W Inc.	1600	106	84	2700K	2.83" x 5.31"
101470	15A21DLED30/G4	★	15	100W Inc.	1600	106	84	3000K	2.83" x 5.31"
102162	15A21DLED40/G4	★	15	100W Inc.	1600	106	84	4000K	2.83" x 5.31"
GU4 Base									
102030	6A19GUDLED27/G4	★	6	40W Inc.	480	80	80	2700K	2.36" x 4.40"
102031	6A19GUDLED30/G4	★	6	40W Inc.	480	80	80	3000K	2.36" x 4.40"
102032	6A19GUDLED40/G4	★	6	40W Inc.	480	80	80	4000K	2.36" x 4.40"
102165	9A19GUDLED27/G4	★	9	60W Inc.	800	88	82	2700K	2.36" x 4.40"
102166	9A19GUDLED30/G4	★	9	60W Inc.	800	88	82	3000K	2.36" x 4.40"
102167	9A19GUDLED40/G4	★	9	60W Inc.	800	88	82	4000K	2.36" x 4.40"
102197	11A19GUDLED27/G4	★	11	75W Inc.	1100	100	83	2700K	2.51" x 4.54"
102198	11A19GUDLED30/G4	★	11	75W Inc.	1100	100	83	3000K	2.51" x 4.54"
102199	11A19GUDLED40/G4	★	11	75W Inc.	1100	100	83	4000K	2.51" x 4.54"
102200	15A21GUDLED27/G4	★	15	100W Inc.	1600	106	84	2700K	2.83" x 5.31"
102201	15A21GUDLED30/G4	★	15	100W Inc.	1600	106	84	3000K	2.83" x 5.31"
102202	15A21GUDLED40/G4	★	15	100W Inc.	1600	106	84	4000K	2.83" x 5.31"

★ ENERGY STAR Certified

COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL	6A19DLEDXX/G4	9A19DLEDXX/G4	11A19DLEDXX/G4	15A21DLEDXX/G4
AH	SDM3/1000/WHTTE 1000W	√	√	√	√
AH	SDM/600/WHTTE 600W	√	√	√	√
ALMOND	LUXDM600-12 600W	√	√	√	X
CTL	DM600-12-3 600W	√	√	√	√
GE	18024 600W	√	√	√	√
LEVITON	6683 600W	√	√	√	X
LEVITON	6631-LA 600W	√	√	√	√
LEVITON	6631-LW	√	√	√	√
LEVITON	6683-IW	√	√	√	√
LEVITON	LIGHT ALMOND NO.6672 600W	√	√	√	X
LEVITON	603-6631-A 600W	√	√	√	√
LEVITON	6631-A 600W	√	√	√	√
LEVITON	WHITE NO.IPL06 600W	√	√	√	X
LEVITON	White/Lvory/Light Almond IPI10-1LZ 600W	√	√	√	X
LEVITON	6683-10Z 600W	√	√	√	X
LEVITON	IPI06-1LZ 600W	√	√	√	X
LUTRON	CTCL-153P	√	√	√	√
LUTRON	DVCL-153P	√	√	√	√
LUTRON	DV-603P600W	X	X	X	√
LUTRON	S-600 600W	X	X	X	√
LUTRON	D-600PH-DK 600W	X	X	X	√
LUTRON	TGCL-153PLH-WH 600W	X	X	X	√
LUTRON	DV-603PR 600W	X	X	X	√
LUTRON	DVW-600PH-WH 600W	X	X	X	√
LUTRON	DV-603PH-WH 600W	X	X	X	√
LUTRON	DV-600PH-WH 600W	X	X	X	√
LUTRON	TG-600PH-IV 600W	X	X	X	√
LUTRON	S-600-AL 600W	X	X	X	√
LUTRON	D-600R-IV 600W	X	X	X	√
LUTRON	DV-603PH-WH 600W	X	X	X	√
LUTRON	LGCL-153P	√	√	√	√
LUTRON	S-603PH-WH 600W	√	√	√	√

√ = Compatible X = Not compatible

Specifications are subject to change without notice.